

# B\_LS-1WR3 Series Power Module List

## SELECTION OF POWER SUPPLY MODULE

Fixed voltage input, isolated non regulated single circuit output 1W

- International standard pins, PCB board installation
- Isolation voltage 1500VDC
- Low ripple coefficient and low noise
- Low static current, high conversion efficiency
- Working temperature -40°C—+85°C



Model	Input Voltage(±10%)	Output Voltage/Current
B0503LS-1WR3		3.3V/303mA
B0505LS-1WR3		5V/200mA
B0509LS-1WR3	5V(4.5V-5.5V)	9V/111mA
B0512LS-1WR3		12V/84mA
B0515LS-1WR3		15V/67mA
B0524LS-1WR3		24V/42mA
B1203LS-1WR3		3.3V/303mA
B1205LS-1WR3		5V/200mA
B1209LS-1WR3	12V(10.8V-13.2V)	9V/111mA
B1212LS-1WR3		12V/84mA
B1215LS-1WR3		15V/67mA
B1224LS-1WR3		24V/42mA
B1203LS-1WR3		3.3V/303mA
B1205LS-1WR3		5V/200mA
B1209LS-1WR3	15V(13.5V-16.5V)	9V/111mA
B1212LS-1WR3		12V/84mA
B1215LS-1WR3		15V/67mA
B1224LS-1WR3		24V/42mA
B2403LS-1WR3		3.3V/303mA
B2405LS-1WR3		5V/200mA
B2409LS-1WR3	24V(21.6V-26.4V)	9V/111mA
B2412LS-1WR3		12V/84mA
B2415LS-1WR3		15V/67mA
B2424LS-1WR3		24V/42mA

※ The picture only for reference, please refer to the actual product