



REVISION RECORD			
REV	ECO	DESCRIPTION	DRFT DATE
Δ		Drawing Revise	Haoyh 03/18/06
Δ		品名、料号增加环保标示“(0)”	CSX 12/10/07
Δ		修改参数	LJH 09/19/08
Δ		修改线径参数	Zengy 01/27/09

- Notes:
1. Pitch: 3.81mm, Poles: 2-XXP
 2. Rated voltage/current: UL 300V/7A
VDE 130V/10A
 3. Operation temperatures: -40℃~+105℃
 4. Withstanding Voltage: AC2000V/1min
 5. Insulation Resistance: 5000MΩ/DC1000V
 6. Wire Range: 24~18AWG, 1.0mm²
 7. Max. Torque Value: M2, 2.04kgf·cm
 8. Undimensioned Tolerances:

Pitch range in mm	Nominal dimension range in mm	over	over	over	over
6 to 10	10 to 30	over	over	over	over
10 to 15	30 to 60	10	60	100	150
15 to 20	60 to 100	24	100	150	
20 to 25	100 to 150				
25 to 30	150 to 200				
30 to 35	200 to 250				
35 to 40	250 to 300				
40 to 45	300 to 350				
45 to 50	350 to 400				
50 to 55	400 to 450				
55 to 60	450 to 500				
60 to 65	500 to 550				
65 to 70	550 to 600				
70 to 75	600 to 650				
75 to 80	650 to 700				
80 to 85	700 to 750				
85 to 90	750 to 800				
90 to 95	800 to 850				
95 to 100	850 to 900				
100 to 110	900 to 1000				

ITEM	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
4	DG330-Screws	5000001400 (H)	XX	Steel	Cr ² N
3	DG350-Spring	X000000290 (H)	XX	Phosphor bronze	Ni plated
2	DG350 (A) Pin header	4017B00010 (H)	XX	Brass	SnCe plated
1	DG340-3.81-Housing	4015A0YXXA (H)	1	PA66	UL94V-0

DETACHED LISTS	
ANGLES ± 1°	±
THIRD ANGLE PROJECTION	

DEGSON 宁波捷正电子有限公司
DEGSON ELECTRONICS CO., LTD

NAME
DG340-3.81-XXP-1Y-00A(H)

DRAWING NO. DG340-3.81-E01

SCALE: 1:1

DO NOT SCALE DRAWING

SHEET 1 OF 1