



Pitch range in mm	over	to	Nominal dimension	over	to	range
6	10	30	60	100	150	—
10	24	30	60	100	150	□
10, 10	15	±0.25	±0.2	±0.3	±0.5	±0.7 ± 1.0, 0.025/10

- Notes:
- Pitch: 3.81mm
 - Rated voltage/current: UL 300V/10A VDE 130V/10A
 - Operation temperatures: -40°C ~ +105°C
 - Withstanding Voltage: AC2000V/1Min
 - Insulation Resistance: 5000MΩ / DC1000V
 - Wire Range: 24 ~ 18AWG, 1.0mm²
 - Max. Torque Value: 2.04kgf·cm
 - Undimensioned Tolerances:

SECTION A-A

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
1	DG340R-3.81-Housing	4016A0VXXA(H)	1	PA66	UL94V-0

DETACHED LISTS

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
4	DG350R-Pin header	4018B00010(H)	XX	Brass	
3	DG350-Screws	S000001400(H)	XX	Steel	Cr ³ -Zn
2	DG350-Sprting	X000000290(H)	XX	Phosphor Bronze	NI plated

DEGSON 宁波捷正电子有限公司
DEGSON ELECTRONICS CO., LTD

NAME: DG340R-3.81-XXP-1Y-00A(H)

DRAWING NO. DG340R-381-E01

SIZE: A3

REV: T3

DD NOT SCALE DRAWING

SHEET 1 OF 1

REVISION RECORD

REV	EQD	DESCRIPTION	DRFT	DATE
Δ		Drawing revise	Haoyh	03/18/08
Δ		图面更新	CSX	05/08/08
Δ		品名、料号增加环保标示“(0)”	CSX	12/10/07

8 7 6 5 4 3 2 1