



*Characteristics:*

*Voltage Rating: 32V*

*Current Rating: 30A Max.*

*Insulation Resistance: 100MΩ Min. at 500VDC*

*Dielectric Strength : AC 1000 V Min.at 60s*

*Fuse type:*

*Medium Blade Fuse: KLS5-270-xxx*

*Order Information:*

*L - KLS5 - 708B -XX R xxx*

*L: RoHS*

*Wire AWG:*

*12- 12AWG for 30A Max.*

*14- 14AWG for 20A Max.*

*16- 16AWG for 15A Max.*

*18- 18AWG for 10A Max.*

*20- 20AWG for 5A Max.*

*Cable Color: R- Red*

*Cable Long: 300-300mm*

3	Cable	UL 1015 PVC Cable 12~20AWG Red,L=300mm	1
2	Terminal	250 Type Female Terminal,Brass T=0.4mm,Nickel Plated	2
1	Housing	Housing For Fuse,Rubber,Black	1
Item	P/N	Describe&Material	Q'ty

GENERAL TOLERANCE	PROJECTION		Description:
X. ±1.00	UNITS	mm	Medium Blade Fuse Holder With Cable
.X ±0.50	Draw by:	Daniel	KLS P/N: L-KLS5-708B-xxR300
.XX ±0.30	Check by:	Daniel	
ANGLE TOLERANCE	Date	2022-09-01	NingBo KLS ELECTRONIC CO.,L TD.
±5°	SHEET	1 OF 1	