



Model: LP103454		Overcharge Detection Voltage(V)	4.28±0.05
Battery pack specification (电池组规格)	Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) ※Single cell capacity (单体电芯容量)	Overdischarge Detection Voltage(V) 过放保护电压 (V)	2.3±0.1
	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) ※Single cell capacity (单体电芯容量)	Limited to Max loading current 仅用于最大的负载电流 peak value (A) constant (A) 峰值 2 (A) 持续 1 (A)	
Ambient Conditions (环境温度)	Charge Temp. 充电温度 (°C)	Customer required Max loading current 客户要求最大的负载电流 peak value (A) constant (A) 峰值 2 (A) 持续 0.5 (A)	
	Discharge Temp. 放电温度 (°C)	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
Humidity (湿度)	Internal impedance 内阻 (≅) (mΩ, AC 1KHZ)	Battery protection (相关的电池保护值)	
	Nominal Voltage 标称电压 (V)	Related Value: (相关的电池保护值)	
	3.7		
	170		
	0~45		
	-20~60		
	65±20%		

EEMB BATTERY		Drawn:	Moyongdi	Revise No.:	E4-2009
Title	LP103454+PCM-LD	Checked 1:	Joanna	Projection:	
File NO.	A04256	Checked 2:	Keyan	Page:	1/1
		Approved:		Scale:	1 : 1.5
		Draw Date:	2011/02/15	Unit:	mm

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).
 2. RoHS compliant (严格按照ROHS要求生产).