



Model: LP103454LC		Overcharge Detection Voltage(V)	4.28±0.05
Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Overdischarge Detection Voltage(V)	3.0±0.1
Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)		Limited to Max loading current 仅用于最大的负载电流 peak value (A) 持续 1 (A)	
Nominal Voltage 标称电压 (V)		Customer required Max loading current 客户要求最大的负载电流 peak value (A) 持续 2 (A)	
Internal impedance 内阻 (≦) (m _Ω , AC 1KHz)		Battery protection (相关的电池保护值)	
Charge Temp. 充电温度 (°C)		Ambient Conditions (环境温度)	
Discharge Temp. 放电温度 (°C)		Humidity (湿度)	
0~45		65±20%	

		Drawn:	lei yuanchao	Revise No.:	E4-2009
Title	LP103454LC-PCM-LD	Checked 1:	Rachel	Projection:	
File NO.	A11074	Checked 2:		Page:	1/1
		Approved:		Scale:	1 : 1
		Draw Date:	2015/03/30	Unit:	mm

Remark(备注):
 1. No scratch, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象)
 2. RoHS compliant(严格按照RoHS要求生产)