



Circuit diagram

Model: LP383454		Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	700	Overcharge Detection Voltage (V) 过充保护电压 (V)	4.28±0.05
Battery pack specification (电池组规格)		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	750	Overdischarge Detection Voltage (V) 过放保护电压 (V)	2.3±0.1
		Nominal Voltage 标称电压 (V)	3.7	Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 (A)	constant (A) 持续 1 (A)
		Internal impedance 内阻 (≅) (mΩ, AC 1KHz)	200	Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A)	constant (A) 持续 0.2 (A)
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45	Battery protection Related Value: (相关的电池保护值) If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
		Discharge Temp. 放电温度 (°C)	-20~60°		
		Humidity (湿度)	65±20%		

		Drawn:	Gongjili	Revise No.:	E4-2009
		Checked 1:	Smile	Projection:	
		Checked 2:		Page:	1/1
		Approved:		Scale:	1:1
		Draw Date:	2012/06/14	Unit:	mm

Title	LP383454-PCM-LD
File NO.	A06540

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).