



Model: LP883450		Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1500
Battery pack specification 电池组规格		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1600
		Nominal Voltage 标称电压 (V)	3.7
		Internal impedance 内阻 (≅) (mΩ, AC 1KHz)	170
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45
		Discharge Temp. 放电温度 (°C)	-20~60
		Humidity (湿度)	65±20%
		Battery protection Related Value: (相关的电池保护值)	
		Overcharge Detection Voltage (V)	4.28±0.05
		Overdischarge Detection Voltage (V)	3.0±0.1
		Overcurrent Protection Voltage (V)	3.0±0.1
		Limited to Max loading current 仅用于最大的负载电流 peak value (A)	constant (A)
		Customer required Max loading current 客户要求最大的负载电流 peak value (A)	持续 1 (A)
		峰值 (A)	持续 (A)
		If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	

Title LP883450-PCM-LD		Drawn: YanF	Revise No.: E4-2009
		Group: Group1	Projection:
File NO. A17056		Approved1:	Page: 1/1
		Approved2:	Scale: 1:1
Draw Date: 2019/04/24		Unit: mm	



Remark(备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).